

Roller Chains (A Series)-3




Features & Advantages



- High Quality Chain Material
- Optimized Heat Treatment Process
- 100% Pre-stretching And Excellent Wear Resistance
- Bush: Made Of High-quality Steel; Case Hardened
- Chain Plate: Made Of High-quality Medium Carbon Steel
- Beveling Porcess For Plate, Quad Riveted Available
- Pin: Made Of High-quality Alloy Steel
- Germany-imported Environment-friendlysuper Wear-resistant Grease
- Copper-plated, Zinc-plated, Nickle-plated And Chrome-plated Chain, Stainlesssteel Chain And Multiple Strands Chain Available

Technical Specifications



Email | sales@hdsusa.us

Tel | +1 (832) 808-5116 Tel | +1 (832) 808-5164



HDS Chain No.		*25-2	*35-2	40-2	50-2	60-2	80-2	100-2	120-2	140-2	160-2	180-2	200-2	240-2
Pitch	P/mm	6.35	9.525	12.70	15.875	19.05	25.40	31.75	38.10	44.45	50.80	57.15	63.50	76.2
Roller Diameter	d2(Max)	3.3	5.08	7.92	10.16	11.91	15.88	19.05	22.23	25.40	28.58	35.71	39.68	47.63
Width Between Inner Plates	b1(Min)	3.10	4.77	7.85	9.40	12.57	15.75	18.90	25.22	25.22	31.55	35.48	37.85	47.40
Pin Diameter	d1(Max)	2.31	3.58	3.96	5.08	5.94	7.92	9.53	11.10	12.70	14.27	17.46	19.84	23.81
Pin Length	L(Max)	21.0	32.6	45.4	57.1	71.5	91.6	111.6	141.0	152.2	181.4	204.4	222.5	271.5
Pin Length	Lc(Max)	21.5	33.5	46.6	58.5	73.2	93.5	115.0	144.2	156.8	185.6	210.2	228.3	278.5
Inner Plate Depth	H2 (Max)	5.90	8.70	12.00	15.00	18.00	24.00	30.10	36.10	42.10	48.10	53.60	60	71.80
Transverse Pitch	Pt	6.40	10.13	14.38	18.11	22.78	29.29	35.76	45.44	48.87	58.55	65.84	71.55	87.83
Ultimate Tensile Strength	KN	10.5	23.7	42.3	66.6	95.4	170.1	265.5	381.0	517.2	680.4	840.7	1061.4	1530.9
Average Tensile Strength	KN	12.4	28.6	50.0	77.8	111.1	198.4	309.6	437.2	593.3	780.6	983.6	1217.8	1756.5
Weight Per Meter	KG/M	0.38	1.0	2.0	3.2	4.7	8	11.9	17.8	22.2	30.65	40.45	54.3	72.6